

Crimp specification				
Type Document	Crimp Specification	Revised /Edition	A3	
Date Issued: 2020/11/18 Data Revised: 2023/09/				
Subject: 2022T-HY2B			Issued By:	
2.0mm	2.0mm Pitch Terminal crimp specification			

Description:


Height and width of conductor crimp core should be set as required.

(conductor crimp height and width of conductor barrel)

According to the external diameter and the type of electric wire, the width of crimped sheath shall be adjusted, wire won't be easily taken off from contact nor too much crimped.

(Crimped width of insulation barrel)

Position Graph:



Note:

- 1. Conductor crimp width. W1
- 2. Conductor crimp height. H1
- 3. Insulator crimp width. W2
- 4. Insulator crimp height. H2
- 5. Conductor wire shall be dimension long (mm) out A.
- 6. Naked part of sheathed wire must be located in the vicinity of center B.
- 7. The Crimp mouth must be equipped like bell.



Crimp specification					
Type Document Crimp Specification Revised /Edition A3					
Date Issued:	Date Issued: 2020/11/18 Data Revised: 2023/09/08				
Subject: 2022T-HY2B	Issued By:				
2.0mm	Pitch Terminal crimp specif	ication	Engineering Dept.		

Requirement:

	Subject:FLRY-A or UL1061 equivalent type electric wire					
AWG#	Conductor (mm²)	Insulation Diameter	Insulator skins length (Dim .B) mm	Copper wire leakage size(Dim .A) mm	Dim. L1 (mm) out	
#26~#24	0.128mm²~0.22mm² 1.40mm(max)		0.40mm~0.80mm	0.5mm(max)	1.90mm~2.10mm	
Wire Gauge	uge Conductor Crimp Area		Insulator	Insulator Crimp Area Terminal Ten		
(AWG#)	Width (W1)	Height(H1)	Width (W2)	Height(H2)	Strength	
#26	1.05±0.03mm	0.63±0.03mm	1.45±0.05mm	1.32±0.05mm	13.7N	
0.22mm ²	1.05±0.03mm		1.45±0.05HIIII -	1.45±0.05mm	40.0N	

Remarks

- 1. Unalike equipment and crimp reel molds skill facility or not shall be difference to result in dissimilar.
- 2. This crimping specification is not limited to material changes.

Signature: _______ENG

Dongguan SESO Technology Co.,Ltd



Crimp specification				
Type Document Crimp Specification Revised /Edition A3				
Date Issued:	2023/09/08			
Subject: 2022T-HY2B	Issued By:			
2.0mm	Pitch Terminal crimp specif	ication	Engineering Dept.	

Date	REV	DESCRIPTION	MODIFY	APPROVAL
2020/11/18	А	Initial Issued	/	Kim Huang
2021/06/18	A1	Modify H1 crimping parameters	FX	Kim Huang
2021/02/17	A2	Change the wire specification	FX	Jack Zhang
2023/09/08	A3	Add A-size data	FX	Jack Zhang



Crimp specification					
Type Document	Type Document Crimp Specification Revised /Edition A6				
Date Issued:	Date Issued: 2020/11/18 Data Revised: 2023/12/16				
Subject: 2022TH	Issued By:				
2.00mm Pitch Terminal crimp specification			Engineering Dept.		

Description:


Height and width of conductor crimp core should be set as required.


(conductor crimp height and width of conductor barrel)

According to the external diameter and the type of electric wire, the width of crimped sheath shall be adjusted, wire won't be easily taken off from contact nor too much crimped.

(Crimped width of insulation barrel)

Position Graph:





Note:

- 1. Conductor crimp width. W1
- 2. Conductor crimp height. H1
- 3. Insulator crimp width. W2
- 4. Insulator crimp height. H2
- 5. Conductor wire shall be dimension long (mm) out A.
- 6. Naked part of sheathed wire must be located in the vicinity of center B.
- 7. The Crimp mouth must be equipped like bell.



Crimp specification						
Type Document	Type Document Crimp Specification Revised /Edition A6					
Date Issued:	Date Issued: 2020/11/18 Data Revised: 2023/12/16					
Subject: 2022TH			Issued By:			
2.00mm	Pitch Terminal crimp specif	fication	Engineering Dept.			

Requirement:

	Subject:FLRY-A or equivalent type electric wire					
AWG#	Conductor (mm²)	Insulation Diameter	Insulator skins length (Dim .B) mm	Copper wire leakage size(Dim .A) mm	Dim. L1 (mm) out	
#24~#22	0.22mm ² ~0.35mm ²	1.50mm(max)	0.40mm~0.80mm	0.5mm(max)	1.90mm~2.10mm	
Wire Gauge	Vire Gauge Conductor Crimp Area Insulator Crimp Area		Terminal Tensile			
(AWG#)	Width (W1)	Height(H1)	Width (W2)	Height(H2)	Strength	
0.22mm ²	1.25±0.03mm	0.71±0.03mm	1.57±0.05mm	1.45±0.05mm	40.0N	
0.35mm ²	1.25±0.0511111	0.78±0.03mm	1.57 ±0.05111111	1.50±0.05mm	50.0N	

Remarks

- 1. Unalike equipment and crimp reel molds skill facility or not shall be difference to result in dissimilar.
- 2. This crimping specification is not limited to material changes.

Signature: <u>JACK</u> ENG

Dongguan SESO Technology Co.,Ltd



Crimp specification						
Type Document	Type Document Crimp Specification Revised /Edition A6					
Date Issued:	Date Issued: 2020/11/18 Data Revised: 2023/12/16					
Subject: 2022TH			Issued By:			
2.00mm	2.00mm Pitch Terminal crimp specification					

Date	REV	DESCRIPTION	MODIFY	APPROVAL
2020/11/18	А	Initial Issued	/	Kim Huang
2021/06/18	A1	Modify H1 crimping parameters	FX	Kim Huang
2023/02/15	A2	Change the wire specification	FX	Jack Zhang
2023/09/04	A3	Modifying H1 dimensions	FX	Jack Zhang
2023/09/08	A4	Add A-size data	FX	Jack Zhang
2023/09/15	A5	Updated 0.22mm ² H1 crimping height	FX	Jack Zhang
2023/12/16	A6	Riveting foot set change	FX	Jack Zhang