

Crimp specification				
Type Document	Crimp Specification	Revised /Edition	А	
Date Issued:	2023/06/08	Data Revised:	2023/06/08	
Subject: 2055T	Issued By:			
2.0mn	Engineering Dept.			

Description:


Height and width of conductor crimp core should be set as required.


(conductor crimp height and width of conductor barrel)

According to the external diameter and the type of electric wire, the width of crimped sheath shall be adjusted, wire won't be easily taken off from contact nor too much crimped.

(Crimped width of insulation barrel)

Position Graph:





Note:

- 1. Conductor crimp width. W1
- $2.\ Conductor\ crimp\ height.\ H1$
- 3. Insulator crimp width. W2
- 4. Insulator crimp height. H2
- 5. Conductor wire shall be dimension long (mm) out A.
- 6. Naked part of sheathed wire must be located in the vicinity of center B.
- 7. The Crimp mouth must be equipped like bell.



Crimp specification					
Type Document	Crimp Specification	Revised /Edition	А		
Date Issued:	2023/06/08	Data Revised:	2023/06/08		
Subject: 2055T	Issued By:				
2.0mm	Engineering Dept.				

Requirement:

Subject: FLRYW-A or equivalent type electric wire							
AWG#	Conductor (mm²)	Insulation Diameter		Insulator skins length (Dim .B) mm		Copper wire leakage size (Dim .A) mm	Dim. L1 (mm) out
#22~#20	0.35~0.50mm²	1.50mm(max)		0	.50mm~1.30mm	0.20mm~0.50mm	3.60mm~4.10mm
Wire Gauge	Conductor Crimp Area		Area	Insulator Crimp Area		Terminal Tensile	
(AWG#)	Width (W1)		Height(H1	.)	Width (W2)	Height(H2)	Strength
0.35mm²	1.45 L0.02mm		0.86±0.03m	ım	1.60mm(may)	1.75±0.05mm	50.0N
0.50mm ² 1.45±0.03mm			0.93±0.03mm 1.60mm(max)		1.00mm(max)	1.90±0.05mm	60.0N

Remarks

- 1. Unalike equipment and crimp reel molds skill facility or not shall be difference to result in dissimilar.
- 2. This crimping specification is not limited to material changes.

Signature:	<i>7</i> X	ENG
Dongguan St	SO Techno	loav CoLtd