



Product Specification [产品规格书]:	Document No:	PS-9020-01
Subject [主题]:	Date Issued	2013/01/10
2.00mm Pitch 9020 Series Connector Specification	Date Revised	2021/03/12
	Version	B

This specification is referred to the 2.00mm series board in connector

索引【INDEX】

1. 适用范围【Scope】
2. 规格与料号【Spec and Part number】
3. 材质与表面处理【Disposal of Material and surface】
4. 额定等级【Ratings and applicable wires】
5. 性能【Performance】
 - 5-1. 电气的性能【Electrical Performance.】
 - 5-2. 机械的性能【Mechanical Performance】
 - 5-3. 环境性能及其它【Environmental Performance and Others】



Product Specification [产品规格书]:	Document No:	PS-9020-01
Subject [主题]:	Date Issued	2013/01/10
2.00mm Pitch 9020 Series Connector Specification	Date Revised	2021/03/12
	Version	B

【1.适用范围 Scope】

此种规格包括 2.00mm Pitch 9020 Series 连接器规格说明。

This Specification Covers the 2.00mm Pitch 9020 Series Connector Specification.

【2.规格与料号 Spec and Part number】

规格内容 Specification	产品料号 Production No.	产品图示 Picture of Product
端子/Terminal	9020TV-PSN-X 9020TR-PSN-X	NONE
胶壳/Housing	9020HV-XX-N0 9020HR-XX-N0	NONE

【3.材质与表面处理 Disposal of Material and surface】

规格内容 Specification	材质 Materials	表面处理 Disposal of Surface
端子/Terminal	磷铜/Phosphor Bronze	Tin Plated: Over 100μ" .Nickel: Over 50μ" .
胶壳/Housing	PA66	UL 94V-0

(上述参数请以工程图为准/Please Refer to the Project drawing for the above Specification)

【4. 额定等级 Ratings and applicable wires】

项目【Item】	规格【Standard】		
额定电压 Rated Voltage (Max.)	250V	[AC/DC]	
额定电流 Rated Current (Max.)	2A		
使用温度范围 Ambient temperature Range	-40°C~+125°C		
适用线径 Applicable wire insulation O.D	9020TV-PSN	AWG#24~26 (0.22~0.13 mm ²)	Insulation O.D. 1.30mm(Max.)
	9020TV-PSN -H	AWG#22~24 (0.35~0.22m m ²)	Insulation O.D. 1.40mm(Max.)

【 *升温时含端子.Including terminal temperature rise. 】



Product Specification [产品规格书]:	Document No:	PS-9020-01
Subject [主题]:	Date Issued	2013/01/10
2.00mm Pitch 9020 Series Connector Specification	Date Revised	2021/03/12
	Version	B

【5.性能 PERFORMANCE】



5-1. 电气的性能 Electrical Performance.

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】
5-1-1	绝缘阻抗 Insulation Resistance	公母配合,在相邻端子,端子与地片之间,使用 500V 的直流电,检测连接器. Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon EIA-364-21B / MIL-STD-202 Method 302 Cond.B)	1000 Megohms Min.
5-1-2	耐电压 Dielectric Strength	公母配合,在相邻端子,端子与地片之间,使用 800V 的交流电 1 分钟,检测连接器. Mate connectors, apply 800V AC for 1 minute between adjacent terminal or ground. (Based upon EIA-364-20A / MIL-STD-202 Method 301)	不出现中断等情况 No Breakdown and Flashover
5-1-3	铆线后端子接 触阻抗 Contact resistance on crimped portion	铆线后之端子,开放电压 20mV 以下,电流 10mA 检测连接器. Crimp the applicable wire on to the terminal measure by dry circuit 20mV MAX, 10mA.	10 milliohms Max.



Product Specification [产品规格书]:	Document No:	PS-9020-01
Subject [主题]:	Date Issued	2013/01/10
2.00mm Pitch 9020 Series Connector Specification	Date Revised	2021/03/12
	Version	B

5-2. 机械的性能 Mechanical Performance.

项目 【Item】	条件 【Test Condition】	规格 【Requirement】			
5-2-1 端子保持力 Terminal/ Housing Retention Force	以每分 25.4±3mm 的速率,将端子从 Housing 内轴向拔出的力量. Apply axial pull out force at the speed rate of 25.4±3mm/minute on the terminal assembled in the housing. 	9.8N {1.0kgf} Min.			
5-2-2 端子插入力 Terminal Insertion Force	铆线后之端子插入 Housing 所需最大力量. Insert the crimped terminal into the housing.	9.8N {1.0kgf} Max.			
5-2-3 端子压着强度 Tensile strength (Crimped connections)	固定铆线后的端子,使电线与端子分离时所需的最小力量. Fix the crimped terminal, apply axial pull out force on the wire. (Do not crimp insulation part).	AWG#	FLY (0.35 mm ²)	FLY (0.22 mm ²)	FLY (0.13m m ²)
		Spec. kgf Min.	50N (75N) ^{a)}	50N	14.7N
		Note> As for unspecified wire sizes in this specification define values with clients			



Product Specification [产品规格书]:	Document No:	PS-9020-01
Subject [主题]:	Date Issued	2013/01/10
2.00mm Pitch 9020 Series Connector Specification	Date Revised	2021/03/12
	Version	B

5-3. 环境性能及其它 Environmental Performance and Others.

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】	
5-3-1	耐热性 Heat Resistance	105±2°C, 96 hours. (Based upon MIL-STD-202 Method 108A Cond.A)	外观 Appearance	无异状 No Damage
5-3-2	耐寒性 Cold Resistance	-40±5°C, 96 hours. (Based upon EIA-364-105)	外观 Appearance	无异状 No Damage
5-3-3	盐水喷雾 Salt Spray	在温度 35±2°C, 盐水浓度 5±1% 下, 盐水喷雾 48±1 小时. 48±1 hours exposure to a salt spray from the 5±1% solution at 35±2°C. (Based upon EIA-364-26B/MIL-STD-202 Method 101D Cond.B).	外观 Appearance	无异状 No Damage
5-3-4	焊锡附着性 Solder- ability	焊接时间: 3~5 秒. 焊接温度: 245±5°C. Soldering Time: 3~5second. Solder Temperature: 245±5°C. (Based upon EIA-364-52)	Solder Wetting	浸渍面积需 95%以上 95% of immersed area must show no voids, pin holes.



Product Specification [产品规格书]:	Document No:	PS-9020-01
Subject [主题]:	Date Issued	2013/01/10
2.00mm Pitch 9020 Series Connector Specification	Date Revised	2021/03/12
	Version	B